



**QUALITY MAT
COMPANY**

Q-LITE MAT
EASY TO WALK ON. SAFE TO WORK ON.
GREAT TO DRIVE ON.

THE MOST VERSATILE GROUND PROTECTION MAT IN THE INDUSTRY.

The Q-Lite Mat is created for both pedestrian and vehicular traffic. The flat, slip-resistant finish assures safe foot traffic without fear of turning an ankle, and vehicles can cross soft terrain without fear of getting stuck. The Q-Lite Mat is ideal for a wide variety of applications wherever pathways, parking areas and vehicle movement are considerations.

FEATURES & BENEFITS

- Dual tread design – pedestrian and traction – offers versatility
- Slip-resistant finish
- Safe to walk on
- Virtually eliminates ground restoration costs from vehicle damage – no rutting
- Limited Lifetime Warranty
- Tough 1/2" thick polyethylene
- Eliminates need for plywood which splinters and warps
- Withstands heavy truck loads
- Prepared for linking together with links
- Easy to handle
- Flexible, conforming to ground variations
- Field tested in extreme cold and heat
- Water and chemical resistant
- Sizes: 4' x 8'
- Can handle up to 120-ton loads

APPLICATIONS / INDUSTRIES

- Tree care industry
- Cemeteries
- Landscape industry
- General construction
- Home movers
- Golf courses
- Movie production companies
- Park and recreation facilities
- Special event contractors and operators
- Rental companies
- Educational facilities
- Municipalities
- Drilling / Boring
- Construction site access



**CREATES STABLE,
NAVIGABLE PATHWAYS**



**WORKS FOR LARGE-AREA
COVERAGE NEEDS**



**PERFECT FOR EVENT
VENUES**



**WORK-SITE SAFETY
AND CLEANLINESS**



QUALITY MAT COMPANY

Q-LITE MAT

EASY TO WALK ON. SAFE TO WORK ON.
GREAT TO DRIVE ON.

EASY TO INSTALL. EASY TO REMOVE.



Flat Turn-a-Links permit locking the mats together to form a roadway or working platform, which makes the Q-Lite Mat ideal for staging, parking or work areas. The mats are tough and flexible, conforming to ground variations, yet they support heavy vehicles crossing soft terrain. Q-Lite Mat virtually eliminates the costs associated with equipment repair and rehabilitating lawns grounds, and subsurface utilities.

For purchasing or pricing please contact your
Quality Mat sales rep: **1.800.227.8159 • QMat.com**



TWO SURFACES FOR ANY NEED

TOP: a pedestrian-friendly 90-degree-plus tread design for foot traffic. **BOTTOM:** a rugged traction diamond plate tread design for equipment.

MATERIAL			
HIGH DENSITY POLYETHYLENE (HDPE)		POST-INDUSTRIAL RECYCLED	
WEIGHT LOAD RATING			
VARIES DEPENDING ON SUB-SURFACE, EQUIPMENT UP TO 120 TONS			
LENGTH	WIDTH	THICKNESS	WEIGHT
8' (2.44M)	4' (1.22M)	1/2" (12.7MM) MAIN SURFACE + 3/8" (9.5MM) TREAD	86 LBS (39 KG)
TEST	ASTM	TYPICAL VALUE	UNITS
MELT INDEX	D1238	<0.10	G/10MIN
SPECIFIC GRAVITY	D792	0.960	
IMPACT STRENGTH	D256	4 - 5	FT-LBS/IN
FLEXURAL MODULUS	D790	160,000	PSI
TENSILE MODULUS	D638	150,000	PSI
TENSILE YIELD STRENGTH	D638	3,500	PSI
ELONGATION @ BREAK	D638	240	%
COMPRESSIVE STRESS @ YIELD	D695	2900	PSI
COLOR OPTIONS			
BLACK - NATURALLY UV RESISTANT		WHITE (ADD'L CHARGE) - WITH UV/AO PROTECTION	CUSTOMER COLOR (MIN REQ. / ADD'L CHARGE)
SHIPPING CONSIDERATIONS			
MAXIMUM 50/PALLET		MAXIMUM 263/20' OCEAN CONTAINER	MAXIMUM 500/40' OCEAN CONTAINER

Full list of specifications available upon request.